

SAFETY DATA SHEET (SDS)

PEG 40 (Hydrogenated Castor Oil)



1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	PEG 40 (Hydrogenated Castor Oil)
Synonyms	:	Polyethyleneglycol monostearate
INCI name	:	PEG-40 Hydrogenated Castor Oil
CAS #	:	61788-85-0
Product use	:	Domestic and Industrial
Supplier	:	ASES CHEMICAL WORKS
Address	:	Brahm Bagh, Jalori Gate Jodhpur - 342001 Rajasthan-India
Telephone Number	:	+91-9636889954
Email & Website	:	Email : ecom@ases.in Website : www.ases.in
Emergency phone number	:	Ph: +91-9636889954 (10.00 to 06.00) Office Hours

2. HAZARDS IDENTIFICATION

Emergency Overview

GHS Classification

Not classified as dangerous goods as per OSHA.

GHS Label elements, including precautionary statements

Signal: Not applicable

Hazard statement(s)

Not applicable.

Precautionary statement(s)

Not applicable.

3. COMPOSITION / INFORMATION INGREDIENTS

Product Name	CAS NO	EC NO	Concentration
No hazardous ingredients.			

4. FIRST AID MEASURES

Eye contact

Immediately flush eyes with plenty of cool water for at least 15 minutes. Get medical attention if irritation occurs.

Skin contact

Remove contaminated clothing. Wash area with soap and water. If irritation occurs, get medical attention.

Inhalation

If inhaled, removed to fresh air. Get medical attention if symptoms appear.

Ingestion

Seek medical attention or contact local poison control center.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media

Water spray, water jet, foam, dry powder, carbon dioxide.

Special protective equipment and precautions for fire-fighters

Wear proper protective equipment. Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.

Special hazards arising from the substance or its combustible products

Hazardous decomposition products may be formed at extreme heat or if burned.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures.

Equip clean crew with proper protection. Respiratory protection equipment may be necessary.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

Methods and materials for containment and cleaning up

Clean up any spills as soon as possible, using an absorbent material to collect it. Use suitable disposal containers.

7. HANDLING AND STORAGE

Precautions for safe handling

No direct lighting. No smoking. Ensure prompt removal from eyes, skin and clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Stainless steel 1.4301 (V2), Stainless steel 1.4401, Stainless steel 1.4571, glass, High density polyethylene (HDPE), Low density polyethylene (LDPE), tinned carbon steel (Tinplate). Keep container tightly closed and dry; store in a cool place. Storage stability: Storage temperature: ≤ 30 °C. Protect against moisture. Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations. Keep container closed when not in use.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eyes

Use tightly sealed goggles.

Skin

If skin contact or contamination of clothing is likely, protective clothing should be worn. Use protective gloves.

Ingestion

Not for ingestion.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	white to yellowish waxy material
Odor	:	Mild odor.
pH	:	6.0 - 7.5
Melting Point/Freezing Point	:	16 - 26 °C (MP)
Flash point	:	242°C

Relative density	:	1.03 g/cm ³ @ 60°C
Solubility (ies)	:	Soluble in water.
Auto-ignition temperature	:	375 °C
Decomposition temperature	:	300 °C

10. STABILITY AND REACTIVITY

Reactivity

This material presents no significant reactivity hazard.

Chemical stability

Chemically stable.

Possibility of hazardous reactions

Hazardous polymerization will not occur.

Conditions to avoid

Avoid sparks, flame and other heat sources.

Incompatible materials

Strong oxidizing agents.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Oral Type of value: LD50 Species: rat Value: > 20,000 mg/kg (BASF-Test)

Inhalation (LC50) : > 2.06 mg/l (OECD Guideline 403)

Carcinogenicity

None of the components of this material are listed as a carcinogen.

Reproductive toxicity

No adverse effects on reproduction are known.

Skin contact

No irritating effect.

Eye contact

Possible irritation should be prevented by wearing safety glasses.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxicity to fish LC50 (48 h) >10,000 mg/l (Oryzias latipes)

Aquatic invertebrates EC50 (48 h) > 100 mg/l (Daphnia magna)

Aquatic plants EC50 (72 h) > 100 mg/l (growth rate) (Desmodemus subspicatus)

Toxicity to microorganisms OECD Guideline 209 aerobic activated sludge, domestic/EC20 (0.5 h): 700 mg/l

Persistence and degradability

Readily degradable. All organic substances contained in the product achieve > 60% BOD / COD or CO₂ liberation.

Bio - accumulative potential

Accumulation in organisms is not to be expected.

Mobility in soil

Not available.

Other adverse effects

Not available.

13. DISPOSAL CONSIDERATION

Dispose of product in accordance with local, state or provincial and federal regulations. Check with local municipal authority to ensure compliance.

14. TRANSPORT INFORMATION

US DOT Shipping Description (Land)

Not regulated

IMO-IMDG Shipping Description (Sea)

Not regulated

IATA Shipping Description (Air)

Not regulated

15. REGULATORY INFORMATION

DSL / NDSL

This product or all of its components are currently listed on the Domestic Substance List (DSL), as described under the Canadian Environmental Protection Act.

California Proposition 65

- This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov.
- This product can expose you to 1,4-Dioxane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.
- This product can expose you to Ethylene Oxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

Disclaimer & Caution

Please refer to all relevant technical information specific to the product, prior to use. The information contained in this document is obtained from current and reliable sources. Provided information contained herein, but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. The user of the product is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties. No representation or warranty, expressed or implied, is made as to the effect(s) of such use(s), (including damage or injury), or the results obtained. The liability is limited to the value of the goods and does not include any consequential loss and shall not be liable for any errors or delays in the content, or for any actions taken in reliance thereon. ASES shall not be responsible for any damages resulting from use of or reliance upon this information.